

ADDITIVO HD 2-10

Additive to improve the mechanical properties and increase the abrasion resistance of ECOSTAR 2K HD per Pavimenti in resina (10:2 catalysis ratio)



Description

ADDITIVO HD 2-10 is an emulsion additive, able to improve the mechanical resistance and increase the abrasion resistance of ECOSTAR 2K HD per Pavimenti in resina (10:2 catalysis ratio).

Characteristics

Appearance	Dense liquid
Coverage	2% maximum in ECOSTAR 2K HD per Pavimenti in resina LD and SL versions 10% maximum for ECOSTAR 2K HD per Pavimenti in resina OP and S.OP versions
Packaging	0,5 Kg
Storage stability	1 year ⁽¹⁾
Tool cleaning	DILUENTE DNH 40 (fresh product)
1 in original sealed containers at temperatures between +10°C and +25°C	

How to use

Shake well before use.

Add under stirring the ADDITIVO HD 2-10 in the quantities listed above for the components A of ECOSTAR 2K HD per Pavimenti in resina (10:2 catalysis ratio).

Check the complete dispersion of the emulsion before catalysis.

Notes:

It is strongly not recommended to add a quantity of additive higher than the aforementioned dose as it would compromise the finish adhesion to the support.

Label elements



· Safety data sheet available on request. Contains Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1); 1,2-BENZISOTIAZOLINA 3(2H)-ONE. May produce an allergic reaction.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_ADDITIVO_HD_2-10.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.