

ADESIVER STE

Single component vinyl alcohol-based adhesive



Description

ADESIVER STE is a single-component vinyl alcohol-based adhesive developed with a mixture of synthetic polymers especially for gluing hard wood floors and pre-finished wooden floor, of any depth. Suitable for gluing on cement agglomerates, gypsum floors, poured asphalt floors, wooden floors. It is NOT suitable for gluing pre-finished wooden floor that is varnished on its back.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	notched trowel n. 7
Pot-Life	n.a.
Maximum open time	3-5' ⁽¹⁾
Hardening	48-72 h ⁽¹⁾
Coverage	900-1200 g/m ² depending on the subfloor.
Colour	beige
Storage stability	1 year ⁽²⁾
Packaging	7 kg - 15 kg
Tool cleaning	DILUENTE DS (before the hardening of the adhesive)

- at 20°C and 65% R.H.
- in original sealed containers at temperatures between +10°C and +25°C

Laying conditions

Subfloor

dry, clean, no-dust creating, not too rough.

Humidity of subfloor

- 2,0% max with cement subfloors.
- 1,7% max with radiant heating cement subfloors.
- 0,5% max with anhydrite subfloors

Wood humidity

9%±2

How to use

Only apply the amount of adhesive that can be covered with wooden floor within 3-5' minutes because of the superficial filmation that can affect the gluing capacity of ADESIVER STE. Spread the adhesive with a notched trowel on the subfloor incorporating any dust present there. Place, level and fix the wooden floor by butting into position to achieve regular anchorage. Perfect adhesion to the subfloor is ensured if at least 65% of each wooden component is in direct contact with the adhesive. When laying down pre-lacquered wooden floors, if a wood piece gets accidentally dirty with glue, clean immediately with DILUENTE PULIPAR or PULIPAR W. We recommend, while using ADESIVER STE, not to smoke and no contact with flame or spark because of the presence of flammable vapour. We recommend to use all the personal prevention systems too.

Warnings

NOT suitable for gluing pre-finished parquet that is varnished on its back.

Label elements

· Highly flammable liquid and vapour. · Suspected of damaging the unborn child. · Causes serious eye irritation. · May cause drowsiness or dizziness.
 · Repeated exposure may cause skin dryness or cracking.
 · Obtain special instructions before use. · Do not handle until all safety precautions have been read and understood. · Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Use only outdoors or in a well-ventilated area. · Wear protective gloves / protective clothing / eye protection / face protection. · IF exposed or concerned: Get medical advice / attention. · Dispose your waste in dedicated collection points.
 Contents: TOLUENE; ACETONE; ETHYL ACETATE; PROPAN-2-OL ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_ADESIVER_STE.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.