

ATTAKKO

Fast vinylic adhesive for skirting boards



Description

ATTAKKO is a special fixing vinyl adhesive to use when a very good start-up sealing is required. As a matter of fact, it is perfect for vertical fittings of baseboards, profiles, etc., on condition that one of the two surfaces soaks the product. ATTAKKO has a quick setting on concrete, stone, brick, pottery, wood and polystyrene. Overpaintable. It does not cause cissings!

Characteristics

| | |
|-------------------------|--|
| Mixture ratio | single-component |
| Application temperature | +10°C ÷ +25°C |
| Application | silicone gun |
| Coverage | 10-15 linear meter / 310 ml |
| | cartridge |
| Maximum open time | 20' ⁽¹⁾ |
| Hardening | 24 h ⁽¹⁾ |
| Colour | white |
| Storage stability | 1 year ⁽²⁾ |
| Packaging | 310 ml |
| Tool cleaning | water (before the hardening of the adhesive) |

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Clean the surfaces to glue. Apply ATTAKKO with a proper gun on one of the two surface to glue drawing a continuous straight line in case of small surface, or a continuous wavy line in case of wider surfaces. Lay within 5 minutes from application, exerting a strong uniform pressure. The setting will be quick. The maximum toughness will be reached within 48 hours. Remove te exceeding still wet with a damp cloth. Caution: minimun temperature for application: +10°C

Label elements



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_ATTAKKO.pdf