

ATTAKKO

Fast vinylic adhesive for skirting boards



Description

ATTAKKO is a special fixing vinyl adhesive to use when a very good start-up sealing is required. As a matter of fact, it is perfect for vertical fittings of baseboards, profiles, etc., on condition that one of the two surfaces soaks the product. ATTAKKO has a quick setting on concrete, stone, brick, pottery, wood and polystyrene. Overpaintable. It does not cause cissings!

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	silicone gun
Coverage	10-15 linear meter / 310 ml
	cartridge
Maximum open time	20' ⁽¹⁾
Hardening	24 h ⁽¹⁾
Colour	white
Storage stability	1 year ⁽²⁾
Packaging	310 ml
Tool cleaning	water (before the hardening of the adhesive)

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Clean the surfaces to glue. Apply ATTAKKO with a proper gun on one of the two surface to glue drawing a continuous straight line in case of small surface, or a continuous wavy line in case of wider surfaces. Lay within 5 minutes from application, exerting a strong uniform pressure. The setting will be quick. The maximum toughness will be reached within 48 hours. Remove te exceeding still wet with a damp cloth. Caution: minimun temperature for application: +10°C

Label elements



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_ATTAKKO.pdf