

ATTAKKO

Fast vinylic adhesive for skirting boards



Description

ATTAKKO is a special fixing vinyl adhesive to use when a very good start-up sealing is required. As a matter of fact, it is perfect for vertical fittings of baseboards, profiles, etc., on condition that one of the two surfaces soaks the product. ATTAKKO has a quick setting on concrete, stone, brick, pottery, wood and polystyrene. Overpaintable. It does not cause cissings!

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	silicone gun
Coverage	10-15 linear meter / 310 ml cartridge
Maximum open time	20' ⁽¹⁾
Hardening	24 h ⁽¹⁾
Colour	white
Storage stability	1 year ⁽²⁾
Packaging	310 ml
Tool cleaning	water (before the hardening of the adhesive)

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Clean the surfaces to glue. Apply ATTAKKO with a proper gun on one of the two surface to glue drawing a continuous straight line in case of small surface, or a continuous wavy line in case of wider surfaces. Lay within 5 minutes from application, exerting a strong uniform pressure. The setting will be quick. The maximum toughness will be reached within 48 hours. Remove te exceeding still wet with a damp cloth. Caution: minimun temperature for application: +10°C.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_ATTAKKO.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsibility of the final result of his work.