

COLOR TECH

Concentrated dyes for ECOFILL TECH



Description

Highly concentrated dyes in aqueous solution, ready to use, characterized by good lightfastness, excellent transparency, gloss and uniformity. Good resistance to overcoating with polyurethane and acrylics. Used to modify and intensify ECOFILL TECH's colour in the presence of dark wood essences.

Characteristics

Appearance	liquid
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	Water
Storage stability	1 year ⁽¹⁾
Packaging	1 L

1 in original sealed containers at temperatures between +10°C and +25°C

Available Versions

Colour Range :

- * Color Tech Brown suitable for brown essences (Iroko, Afromosia, Walnut, Teak, Ipe Lapacho.)
- * Color Tech Red Brown suitable for red essences (Doussie, Cherry, Merbau, Padouk, Douglas ..)
- * Color Tech Wengé specific for Wengé

How to use

Shake COLOR TECH before adding it to ECOFILL TECH. Add COLOR TECH, in the maximum percentage of 5%, mixing carefully until a homogeneous color is obtained. Mix with wood powder (see ECOFILL TECH's data sheet).

Label elements

CTEC000X	Color	· Flammable liquid and vapour.
	Tech	· Contains . May produce an allergic reaction.
	Red	· · · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. In case of fire: use water to extinguish. Avoid breathing dust / fume / gas / mist / vapours / spray. If skin irritation or rash occurs: Get medical advice / attention.
	Brown	Contents: CAS: 84989-26-4 ;



CTEC001X	Color	· Flammable liquid and vapour.
	Tech	· Contains . May produce an allergic reaction.
	Brown	· · · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. In case of fire: use water to extinguish. Avoid breathing dust / fume / gas / mist / vapours / spray. If skin irritation or rash occurs: Get medical advice / attention.
		Contents: CAS: 57693-14-8 CAS: 84989-26-4 ;



CTEC002X	Color	· Flammable liquid and vapour.
	Tech	· Contains . May produce an allergic reaction.
	Wengé	· · · · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. In case of fire: use water to extinguish. Avoid breathing dust / fume / gas / mist / vapours / spray. If skin irritation or rash occurs: Get medical advice / attention.
		Contents: CAS: 57693-14-8 CAS: 84989-26-4 ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_COLOR_TECH.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.