

DILUENTE DMC 50

Pure thinner for polyurethane varnishes



Description

DILUENTE DMC 50 is an anhydrous thinner for polyurethane varnishes.

Characteristics

Appearance	colourless liquid
Specific weight	0,87 kg/lt
Packaging	5-10-12,5-25 lt
Storage stability	1 year ⁽¹⁾

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

This product has to be used to dilute varnishing products; suitable also for primers and polyurethane adhesives. For suitable use in each product, please read its technical data sheet.

Label elements

· Highly flammable liquid and vapour.· Causes skin irritation.· May cause drowsiness or dizziness.

· Repeated exposure may cause skin dryness or cracking.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Keep container tightly closed.· Wash thoroughly with water after use.· Wear protective gloves / protective clothing / eye protection / face protection.· IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.· Call a POISON CENTER or doctor / physician if you feel unwell.

Contents: N-BUTYL ACETATE ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_DILUENTE_DMC_50.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.