

DILUENTE DS

Thinner for tool-cleaning and dilution of epoxy-polyurethane primers and adhesives



Description

DILUENTE DS is a special thinner for removing fresh remains of epoxy-polyurethane two-component adhesives. Also good for diluting adhesives.

Characteristics

Appearance	pink liquid
Specific weight	0,789 kg/lit
Packaging	1L -5L -10L
Storage stability	1 year ⁽¹⁾

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Thinner suggested for the dilution of epoxy-polyurethane primers and adhesives. For specific use in each product consult the respective technical data sheets.

Also suitable for cleaning tools used in laying parquet.

Label elements

- Highly flammable liquid and vapour. · Causes serious eye irritation.
- Repeated exposure may cause skin dryness or cracking.
- If medical advice is needed, have product container or label at hand. · Keep out of reach of children. · Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Wear protective gloves / protective clothing / eye protection / face protection. · If eye irritation persists: Get medical advice / attention. · Dispose your waste in dedicated collection points.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_DILUENTE_DS.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.