

LIOS NATURAL WAX

Natural waxes blend for the treatment of wooden floors



Description

LIOS NATURAL WAX is a natural wax blend recommended for the treatment of wooden floors, cotto floors and furnitures. The treated materials have an excellent superficial hardness and glossiness. The waxed floors whitening, due to water absorption, is reduced by using natural waxes.

Characteristics

| | |
|-------------------------|---------------------------------------|
| Mixture ratio | single-component |
| Application temperature | +10°C ÷ +25°C |
| Application | rubber trowel, cloth, buffing machine |
| Surface dry time | 12-24 h ⁽¹⁾ |
| Total drying time | 2 weeks ⁽¹⁾ |
| Thinning (if necessary) | LIOS SOLV |
| Coverage | 1 L / 25-30 m ² |
| Storage stability | 1 year ⁽²⁾ |
| Packaging | 1 L - 5 L |
| Tool cleaning | LIOS SOLV (with fresh product) |

- 1 at 20°C and 65% R.H.
 2 in original sealed containers at temperatures between +10°C and +25°C

How to use

LIOS NATURAL WAX has to be applied to wooden floors that have been filled and sanded with 100/120 paper grit, than use High Pro felt disc to make the surface absorbs the product evenly. Alternatively, finish the floor with 150 paper grit. Apply LIOS NATURAL WAX by cloth or buffing machine on the floor, working the product in order to help its penetration into the wood grain, without leaving any excess of product.

After 15-20 minuts buff the surfaces using a buffing machine with a white pad and a cloth to remove the excess of oil and have an uniform and smooth effect.

The best result is obtained after the application of 2/3 coats of LIOS NATURAL WAX.

Application on cotto tiles:

Apply LIOS NATURAL WAX by cloth or buffing machine, working the product in order to help its penetration into the wood grain, without leaving any excess of product. If the desired result has not been obtained, it is suggested to apply another coat of LIOS NATURAL WAX. In case of strongly absorbent floors, it is advisable to apply WAX CARE (see relative technical data sheet).

Maintenance

Remove by cloth, using LIOS SOLV (see relative technical data sheet) if present, any sole black marks. Apply by cloth LIOS NATURAL WAX diluted with LIOS SOLV in ratio 1:1, after the complete drying it is possible to buff the surface.

The ordinary and extraordinary maintenance have to be done with VELUREX CLEANER STAR SUPER AZIONE SANIFICANTE (see relative technical data sheet).

Warnings

Keep out of children's reach. Do not drink nor inhale. Avoid contact with eyes.

Label elements

- Flammable liquid and vapour.· May be fatal if swallowed and enters airways.· May cause drowsiness or dizziness.
 - Repeated exposure may cause skin dryness or cracking.
 - Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Keep container tightly closed.· Wear protective gloves / protective clothing / eye protection / face protection.· IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.· IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Contents:NAPHTA (PETROL.) HYDROTREATED HEAVY ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_NATURAL_WAX.pdf