

VELUREX Metal Matt

High resistance matt wax for the maintenance of varnished wooden floors



Description

VELUREX Metal Matt is a pre-metallized wax for the intense maintenance of ruined and/or abraded lacquered wooden floors, resilient and resin floors. The film of VELUREX Metal Matt is characterised by long lasting, hardness and transparency giving a matt look to the surface treated.

Characteristics

Application temperature	+10°C ÷ +25°C
Application	microfiber cloth
Thinning (if necessary)	water
Coverage	1 L / 40-70 m ²
Storage stability	1 year ⁽¹⁾
Packaging	1 L
Tool cleaning	water

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Clean very well the floor with VELUREX Cleaner Star (see technical data sheet) and let it dry.

Spread VELUREX Metal Matt uniformly and evenly on the surface using a microfiber cloth. For particularly heavily used floors apply a second coat of VELUREX Metal Matt after the first coat has completely dried (about 2 hours). After some applications of VELUREX Metal Matt it is advisable to remove the old layers of wax with VELUREX Sgrassatore (see relative technical data sheet), rinse very well with water and let it dry. Proceed with the application of VELUREX Metal Matt from the beginning.

Warnings

Keep out of children's reach. If medical advice needed, have product container or label at hand.

Label elements



- Safety data sheet available on request. - Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_VELUREX_Metal_Matt.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.